



İNCE ETLİ KARE VE DİKDÖRTGEN PROFİLLERİ (TS 6475)

KENAR UZUNLUĞU			Birim Ağırlıkları (kg/m)							
h Anma Boyutu	b Anma Boyutu	h ve b için toleranslar	1	1.25	1.5	2	2.5	3	4	
15	15	±0.20	0.438	0.537	0.632	0.810				
18	18	±0.20	0.532	0.655	0.773	0.998				
20	10	±0.20	0.438	0.537	0.632	0.810				
	15		0.516	0.635	0.750	0.967				
	20		0.595	0.733	0.868	1.12	-			
25	15	±0.25	0.595	0.733	0.868	1.12	-	-		
	25		0.752	0.930	1.10	1.44	-	-		
30	10	±0.25	0.595	0.733	0.868	1.12	-	-		
	15		0.673	0.831	0.985	1.28	-	-		
	20		0.752	0.930	1.10	1.44	-	-		
	30		0.909	1.13	1.34	1.75	2.15	2.39	-	
34	20	±0.25	0.815	1.01	1.20	1.56	-	-	-	-
	34		1.03	1.28	1.53	2.00	2.46	2.77	-	-
35	20	±0.25	0.830	1.03	1.22	1.59	1.95	-	-	
	25		0.909	1.13	1.34	1.75	2.15	2.39	-	-
	35		1.07	1.32	1.57	2.07	2.54	2.86	-	-
36	11	±0.25	0.705	0.871	1.03	1.34	-	-	-	
40	20	±0.30			1.34	1.75	2.15	2.39	-	-
	25				1.46	1.91	2.34	2.63	-	-
	30				1.57	2.07	2.54	2.86	-	-
	40				1.81	2.38	2.93	3.33	4.25	-
45	45	±0.30			2.05	2.69	3.33	3.80	4.88	-
50	20	±0.30			1.57	2.07	2.54	2.86	-	-
	25				1.69	2.22	2.74	3.10	-	-
	30				1.81	2.38	2.93	3.33	4.25	-
	34				1.90	2.51	3.09	3.52	4.50	-
	40				2.05	2.69	3.33	3.80	4.88	-
50			2.28	3.01	3.72	4.28	5.51	-		
55	34	±0.40			2.02	2.66	3.29	3.76	4.82	-
60	20	±0.40				2.38	2.93	3.33	-	-
	30				2.69	3.33	3.80	4.88	-	
	40				3.01	3.72	4.28	5.51	-	
	50				3.32	4.11	4.75	6.14	-	
60			3.64	4.50	5.22	6.76	8.13	-		
70	40	±0.50				3.32	4.11	4.75	6.14	-
	70				4.26	5.29	6.16	8.02	9.70	-
80	20	±0.60				3.01	3.72	4.28	-	-
	30				3.32	4.11	4.75	-	-	
	40				3.64	4.50	5.22	6.76	8.13	
	50				3.95	4.90	5.69	7.39	8.91	
	60				4.26	5.29	6.16	8.02	9.70	
	80				4.89	6.07	7.10	9.28	11.3	
90	90	±0.75				5.52	6.86	8.04	10.5	12.8
100	40	±0.80				4.26	5.29	6.16	8.02	9.70
	50				4.58	5.68	6.63	8.65	10.5	
	60				4.89	6.07	7.10	9.28	11.3	
	80				5.52	6.86	8.04	10.5	12.8	
	100				6.15	7.64	8.99	11.8	14.4	
120	40	±0.80				4.89	6.07	7.10	9.28	11.3
	60				5.52	6.86	8.04	10.5	12.8	